



Finished Size: **44" x 64" (1.12m x 1.63m)** Fabric Collection Name and Fabric Designer: **Space Cadet by Francesco Moretti** Technique: **Pieced** Designed by: **Denise Russell of Pieced Brain** Skill Level: **Beginner** Tech Edited by: **Lisa Visel, Mountain View Quilts**



Fabric Requirements

DESIGN	CO	LOR	ITEM ID		YARDAGE		
(A) Moon	Bla	ck	4361-99		½ yard (0.46m)		
(B) Planets	Na	ЛУ	4364-78	1	yard (0.91m	1)	
(C) Panel	Bla	ck	4368P-99	2/3	yard (0.61m	า)	
(D) Chameleon	lvo	ry	1178-41		¼ yard (0.23m)		
(E) Chameleon	Yel	low	1178-43	1⁄4	¼ yard (0.23m)		
(F) Chameleon	Lt.	Gray	1178-90		¼ yard (0.23m)		
(G) Chameleon	on Cha		1178-95	¼ yard (0.23m)		า)	
(H) Chameleon	Bla	ck	1178-99	1/2	½ yard (0.46m)		
(I) Starlet	Na	ЛУ	6383-Navy*	% yard (0.57m)			
* includes binding							
(A) (B)	(C) (D)	(E)	(F)	(G)	(H)	(1)	
Backing (Purchased Separately)							
44" (1.12m) wide Astronauts OR		ck	4365-99		27⁄8 yards (2.63m)		
108" (2.74m) wide 1½ yards						7m)	



Backing 44"

Additional Materials:

- 100% cotton thread in colors to match
- Batting: 52" x 72" (1.32m x 1.83m)
- · Thread and sewing supplies

All possible care has been taken to ensure the accuracy of this pattern. We are not responsible for printing errors or the manner in which individual work varies. Please read the instructions carefully before starting this project. If kitting it is recommended a sample is made to confirm accuracy.



Cutting

Notes:

- Please make sure to check *www.blankquilting.net* for pattern updates prior to starting the project.
- All strips are cut across the width of fabric (WOF) from selvage to selvage edge unless otherwise noted.

Fabric A, cut: (4) 3" x WOF for border

Fabric B, cut: (5) 5" x WOF for border 8

Fabric C: Trim panel to 19½" x 39½"

Fabric D, cut: (4) 1¹/₄" x WOF for border 1

Fabric E, cut: (5) 1¹/₄" x WOF for border 7 **Fabric F, cut**: (4) 1½" x WOF for border 2

Fabric G, cut: (4) 1½" x WOF for border 3

Fabric H, cut: (4) 1½" x WOF for border 4 (5) 1½" x WOF for border 6

Fabric I, cut: (6) 2¹/₂" x WOF for binding

All possible care has been taken to ensure the accuracy of this pattern. We are not responsible for printing errors or the manner in which individual work varies. Please read the instructions carefully before starting this project. If kitting it is recommended a sample is made to confirm accuracy. All free projects are intended to remain free and are not for resale.



Quilt Top Assembly

Note: Follow the Quilt Layout Diagram (page 5) while assembling the quilt top.

- For border 1, measure the vertical length of the panel through the center and cut (2) 1¼"
 Fabric D border strips that length. Sew (1) strip to each side of the quilt and press the seams toward the borders. Measure the width of the quilt through the center. Cut (2) border strips that length and sew (1) to the top and (1) to the bottom. Press the seams toward the borders.
- 2. For border 2, sew (4) 1½" Fabric F border strips together end to end using diagonal seams. Measure the vertical length of the quilt top through the center and cut (2) border strips that length. Sew (1) strip to each side of the quilt top and press the seams toward the borders. Measure the width of the quilt top through the center. Cut (2) border strips that length and sew (1) to the top and (1) to the bottom. Press the seams toward the borders.
- 3. Repeat step 2 with (4) 1¹/₂" **Fabric G** strips to make and add border 3.
- 4. Repeat step 2 with (4) 1¹/₂" **Fabric H** strips to make and add border 4. Quilt should measure approximately 25" x 45".
- 5. Repeat step 2 with (5) 3" **Fabric A** strips to make and add border 5.
- 6. Repeat step 2 with (5) 1½" **Fabric H** strips to make and add border 6.
- 7. Repeat step 2 with (5) 1¹/₄" **Fabric E** strips to make and add border 7.
- 8. Repeat step 2 with (6) 5" **Fabric B** strips to make and add border 8. Quilt should measure approximately 44½" x 64½".

Finishing

- 9. Sew together the (6) 2½" **Fabric I** binding strips end to end using diagonal seams. Press the seams open. Press the binding strip in half with the wrong sides together.
- 10. Layer the backing (wrong side up), batting, and quilt top (right side up). Baste the layers together and quilt as desired. Trim excess batting and backing even with the top of the quilt.
- 11. Leaving an 8" tail of binding and beginning along an edge of the quilt top, matching the raw edges of the binding to the raw edges of the quilt. Sew the binding to the outside edge around all four sides and miter corners. Stop sewing approximately 12" from where you started and backstitch.
- 12. Lay both loose ends of the binding flat along the quilt edge. Where these two loose ends meet, fold them back onto themselves and press to form a crease. Using this crease as your stitching line, sew the two open ends of the binding together, with the right sides matching. Trim the seam to ¼" and press it open. Finish sewing the binding to the quilt.
- 13. Turn the binding over the raw edge to the back of the quilt and hand or machine stitch in place.







All possible care has been taken to ensure the accuracy of this pattern. We are not responsible for printing errors or the manner in which individual work varies. Please read the instructions carefully before starting this project. If kitting it is recommended a sample is made to confirm accuracy.