



Finished Size of Project: Runner - 96" x 20" (2.43m x 0.51m)

Place Mats - 22" x 14" (0.56m x 0.36m)

Fabric Collection Name and Designer: **Be Merry & Shine Bright by Lily Ford** 

Technique: Pieced

Project Designed by: Matthew Pridemore of The Whimsical Workshop

Skill Level: **Advanced Beginner** 

Copyright© 2025



## **Runner Fabric Requirements**


DESIGN	COLOR	ITEM ID	YARDAGE
(A) Christmas Bells	Charcoal	4117-95	3⁄4 yard (0.34m)
(B) Christmas Blocks	Charcoal	4119-95	¾ yard (0.61m)
(C) Christmas Floral	Charcoal	4120-95	¾ yard (0.34m)
(D) Snowflakes	Charcoal	4121-95	½ yard (0.46m)
(E) Bells and Poinsettias	Charcoal	4127-95	¾ yard (0.34m)
(F) Intermix	Olive	3188-65	¾ yard (0.34m)
(G) Intermix	Red	3188-88	1½ yards (1.37m)*

<sup>\*</sup> includes binding















**Backing** (Purchased Separately)

44" (1.12m) wide Christmas Ornaments

Charcoal

4123-95

3 yards (2.74m)



Backing 44"

#### **Additional Materials:**

- Batting 104" x 28" (2.64m x 0.71m)
- Thread and sewing supplies



## **Runner Cutting Instructions**

#### Notes:

- Please make sure to check blankquilting.net for pattern updates prior to starting the project.
- All strips are cut across the width of fabric (WOF) from selvage to selvage edge unless otherwise noted.

#### Fabric A, cut:

(1) 11½" x WOF; subcut (1) 11½" square

### Fabric B, fussy cut:

(3) 11½" squares, each centered on a dark block

### Fabric C, cut:

(1) 11½" x WOF; subcut (1) 11½" square

# Fabric D, cut:

- (1) 2" x WOF; subcut (2) 2" x 14½"
- (3) 1½" x WOF; subcut (5) 1½" x 14½"
- (5) 1%" x WOF. Sew the strips together end to end with diagonal seams and cut (2) 1%" x 92%"

### Fabric E, cut:

(1) 11½" x WOF; subcut (1) 11½" square

#### Fabric F, cut:

(4) 21/2" x WOF

#### Fabric G, cut:

- (4) 21/2" x WOF
- (2) 2½" x WOF; subcut (6) 2½" x 11½"
- (3) 2½" x WOF; subcut (6) 2½" x 15½"
- (2) 2" x WOF; subcut (6) 2" x 11½"
- (3) 2" x WOF; subcut (6) 2" x 14½"
- (6) 2½" x WOF for the binding

## Backing, cut:

(1) 104" x 28" WOF



### **Runner Sewing**

- Sew using a ¼" seam allowance with right sides together (RST) unless otherwise indicated. Press seams towards the darker fabric, unless otherwise indicated.
- The arrows in the figures represent the fabric print direction. Pay attention to the fabric and unit orientations when assembling the various components.
- 1. Sew (1) 2½" x 11½" **Fabric G** strip to each side of (1) 11½" **Fabric B** square. Sew (1) 2½" x 15½" **Fabric G** strip to the top and bottom of the **Fabric B** square to make (1) Block One square (**Fig. 1**). **Trim the block to measure 14½" x 14½".** Repeat to make (3) Block One squares total.

Fig. 1

Block One
make 3

G

Trim block
to measure
14 ½" x 14 ½"
AFTER adding
Fabric G borders

2. Sew (1) 2" x 11½" **Fabric G** strip to each side of (1) 11½" **Fabric A** square. Sew (1) 2" x 14½" **Fabric G** strip to the top and bottom of the **Fabric A** square to make (1) 14½" Block Two square (**Fig. 2**).

Fig. 2


Block Two

G


A

G

3. Sew (1) 2" x 11½" **Fabric G** strip to each side of (1) 11½" **Fabric E** square. Sew (1) 2" x 14½" **Fabric G** strip to the top and bottom of the **Fabric E** square to make (1) 14½" Block Three square (**Fig. 3**).




4. Sew (1) 2" x 11½" **Fabric G** strip to each side of (1) 11½" **Fabric C** square. Sew (1) 2" x 14½" **Fabric G** strip to the top and bottom of the **Fabric C** square to make (1) 14½" Block Four square (**Fig. 4**).




x 14½" **Fabric D** strip, (1) Block Two square, (1) 1½" x 14½" **Fabric D** strip, (1) Block Two square, (1) 1½" x 14½" **Fabric D** strip, (1) Block One square, (1) 1½" x 14½" **Fabric D** strip, (1) Block Three square, (1) 1½" x 14½" **Fabric D** strip, (1) Block One square, (1) 1½" x 14½" **Fabric D** strip and (1) Block Four square, in that order from left to right, to make the 89½" x 14½" Runner Center Block (**Fig. 5** on page 5).



- 6. Sew together (2) 2½" x WOF **Fabric G** strips and (2) 2½" x WOF **Fabric F** strip, lengthwise and alternating them from left to right, to make (1) Strip Set 1 (**Fig. 6**). Repeat to make a second Strip Set 1.
- 7. Cut the (2) Strip Set 1's into (28) 2½" x 8½" Unit 1 strips (**Fig. 7**).



- 8. Sew together (2) Unit 1 strips to make the Left Side Border (**Fig. 8**).
- 9. Sew together (2) Unit 1 strips to make the Right Side Border (**Fig. 9**).




- 10. Sew together (12) Unit 1 strips end-to-end to make the Top Border (**Fig. 10** below).
- 11. Sew (12) Unit 1 strips together end-to-end to make the Bottom Border (**Fig. 11** below).

### **Runner Top Assembly**

Follow the Runner Layout (Page 6) while assembling the runner top.

- 12. Sew (1) 2" x 14½" **Fabric D** strip to each side of the Runner Center Block.
- 13. Sew (1) 1½" x 92½" **Fabric D** strip to the top and bottom of the Runner Center Block.
- 14. Sew the Left Side Border and Right Side



Unit 1 Unit

Fig. 11

| Tinu |



- Borders to the left and right sides of the Runner Center Block.
- 15. Sew the Top Border and the Bottom Border to the top and to the bottom of the Runner Center Block to make the Runner top which should measure 96½" x 20½".


# Runner Layering, Quilting and Finishing

16. Layer the backing (wrong side up), batting, and runner top (right side up). Baste the layers together and quilt as desired. Trim excess batting and backing even with the top of the runner.

## **Runner Binding**

17. Sew together (6) 2½" x WOF **Fabric G** binding strips end to end with diagonal seams. Press the seams open. Press the binding strip in half wrong sides together.

- 18. Leaving an 8" tail of binding and beginning along an edge of the runner top, match raw edges of the binding to the raw edges of the runner top. Sew the binding to the outside edge around all four sides and miter corners. Stop sewing approximately 12" from where you started and backstitch.
  - 19. Lay both loose ends of binding flat along the runner edge. Where these two loose ends meet, fold them back onto themselves and press to form a crease. Using this crease as your stitching line, sew the two open ends of the binding together, right sides matching. Trim seam to ¼" and press seam open. Finish sewing the binding to the runner top.
  - 20. Turn the binding over the raw edge to the back of the runner and hand or machine stitch in place.



Copyright© 2025 6 of 11



# Place Mat Fabric Requirements (makes 6)

COLOR	ITEM ID	YARDAGE
White	4118-01	% yard (0.34m)
Charcoal	4119-95	¾ yard (0.61m)
Charcoal	4121-95	¾ yard (0.69m)
White	4125-01	% yard (0.34m)
White	4126-01	% yard (0.34m)
Olive	3188-65	1 yard (0.91m)*
Red	3188-88	1 yard (0.91m)*
	White Charcoal Charcoal White White Olive	White4118-01Charcoal4119-95Charcoal4121-95White4125-01White4126-01Olive3188-65

<sup>\*</sup> includes binding















**Backing** (Purchased Separately)

44" (1.12m) wide

Plaid Charcoal 4124-95 2¼ yards (2.06m)



Backing

#### **Additional Materials:**

- Batting (6) 26" x 18" (0.66m x 0.46m)
- · Thread and sewing supplies



## **Place Mat Cutting Instructions**

#### Notes:

- Please make sure to check blankquilting.net for pattern updates prior to starting the project.
- All strips are cut across the width of fabric (WOF) from selvage to selvage edge unless otherwise noted.

#### Fabric A, cut:

(1) 11½" square

#### Fabric B, fussy cut:

(3) 11½" squares, each centered on the light blocks

#### Fabric C, cut:

- (2) 2½" x WOF; subcut
  - (6) 2½" x 11½"
- (3) 21/2" x WOF; subcut
  - (6) 2½" x 15½"
- (2) 2" x WOF; subcut
  - (6) 2" x 11½"
- (3) 2" x WOF; subcut
  - (6) 2" x 141/2"

### Fabric D, cut:

(1) 11½" square

## Fabric E, cut:

(1) 11½" square

#### Fabric F, cut:

- (6) 21/2" x WOF
- (6) 21/2" x WOF for the binding

#### Fabric G, cut:

- (6) 21/2" x WOF
- (6) 21/2" x WOF for the binding

#### Backing, cut:

(6) 26" x 18" WOF



### **Place Mat Sewing**


- Sew using a ¼" seam allowance with right sides together (RST) unless otherwise indicated. Press seams towards the darker fabric, unless otherwise indicated.
- The arrows in the figures represent the fabric print direction. Pay attention to the fabric and unit orientations when assembling the various components.
- 21. Sew (1) 2½" x 11½" **Fabric C** strip to each side of (1) 11½" **Fabric B** square. Sew (1) 2½" x 15½" **Fabric C** strip to the top and bottom of the **Fabric B** square to make (1) Block Five square (**Fig. 13**). **Trim the block to measure 14½" x 14½".** Repeat to make (3) Block Five squares total.

Fig. 13


Block Five make 3

Trim block to measure 14 ½" x 14 ½" AFTER adding Fabric C borders


22. Sew (1) 2" x 11½" **Fabric C** strip to each side of (1) 11½" **Fabric E** square. Sew (1) 2" x 14½" **Fabric C** strip to the top and bottom of the **Fabric E** square to make (1) 14½" Block Six square (**Fig. 14**).



- 23. Sew (1) 2" x 11½" **Fabric C** strip to each side of (1) 11½" **Fabric D** square. Sew (1) 2" x 14½" **Fabric C** strip to the top and bottom of the **Fabric D** square to make (1) 14½" Block Seven square (**Fig. 15**).
- 24. Sew (1) 2" x 11½" **Fabric C** strip to each side of (1) 11½" **Fabric A** square. Sew (1) 2" x 14½" **Fabric C** strip to the top and bottom of the **Fabric A** square to make (1) 14½" Block Eight square (**Fig. 16**).



- 25. Sew (1) 2½" x WOF **Fabric G** strip to the left side of (1) 2½" x WOF **Fabric F** strip lengthwise to make (1) Strip Set 2 (**Fig. 17**). Repeat to make (6) Strip Set 2's total.
- 26. Cut the (6) Strip Set 2's into (84) 2½" x 4½" Unit 2 strips (**Fig. 18**).





27. Paying attention to the orientation of 29. Repeat Step 28 and refer to Figures 21-23 the units, sew together (7) Unit 2 strips lengthwise to make (1) Block Nine strip (Fig. 19). Repeat to make (12) Block Nine strips total.

Fig. 19 **Block Nine** make 12 Unit 2 Unit 2 Unit 2 Un<mark>it 2</mark> Unit 2

Unit 2 Unit 2

# **Place Mat Top Assembly**

Follow the Place Mat Layouts while assembling the place mat tops.

28. Sew (1) Block Nine strip to each side of (1) Block Five square to make (1) Place Mat #1 top which should measure 22½" x 14½" (Fig. 20). Repeat to make (3) Place Mat #1 tops total.

Fig. 20 Place Mat Layout #1 make 3


for component identification, placement and orientation to make (1) Place Mat #2 top, (1) Place Mat #3 top and (1) Place Mat #4 top.

Place Mat Layout #2 6

Fig. 21

Place Mat Layout #3

Fig. 22





# Place Mat Layering, Quilting and Finishing

30. Layer (1) backing (wrong side up), (1) batting, and (1) place mat top (right side up). Baste the layers together and quilt as desired. Trim excess batting and backing even with the top of the runner. Repeat with the remaining batting, place mat tops and backs.

## **Place Mat Binding**

- 31. Sew together (6) 2½" x WOF **Fabric G** binding strips end to end with diagonal seams. Press the seams open. Press the binding strip in half, wrong sides together.
- 32. Leaving an 8" tail of binding and beginning along an edge of (1) place mat #1 top, match raw edges of the binding to the raw edges of the place mat top. Sew the binding to the outside edge around all four sides and miter corners. Stop sewing approximately 12" from where you started and backstitch.
- 33. Lay both loose ends of binding flat along the place mat edge. Where these two loose ends meet, fold them back onto themselves and press to form a crease. Using this crease as your stitching line, sew the two open ends of the binding together, right sides matching. Trim seam to ¼" and press seam open. Finish sewing the binding to the place mat top.
- 34. Turn the binding over the raw edge to the back of the place mat and hand or machine stitch in place. Repeat with the remaining (2) Place Mat #1 tops and **Fabric G** binding strips.

- 35. Sew together (6) 2½" x WOF **Fabric F** binding strips end to end with diagonal seams. Press the seams open. Press the binding strip in half, wrong sides together.
- 36. Leaving an 8" tail of binding and beginning along an edge of (1) place mat #2 top, match raw edges of the binding to the raw edges of the place mat top. Sew the binding to the outside edge around all four sides and miter corners. Stop sewing approximately 12" from where you started and backstitch.
- 37. Lay both loose ends of binding flat along the place mat edge. Where these two loose ends meet, fold them back onto themselves and press to form a crease. Using this crease as your stitching line, sew the two open ends of the binding together, right sides matching. Trim seam to ¼" and press seam open. Finish sewing the binding to the place mat top.
- 38. Turn the binding over the raw edge to the back of the place mat and hand or machine stitch in place. Repeat with the Place Mat #3 and Place Mat #4 tops and remaining **Fabric F** binding strips.