



Finished Size of Project: **60" x 72" (1.52m x 1.83m)** Fabric Collection Name and Designer: **Front Porch Charm by Satin Moon Designs** Technique: **Pieced** Project Designed by: **Denise Russell of Pieced Brain** Skill Level: **Advanced Beginner**



Fabric Requirements

	-qui cinc				
DESIGN			COLOR	ITEM ID	YARDAGE
(A) Lattice Geometric		White	4694-01	¾ yard (0.69m)	
(B) Lattice Geometric		Blue	4694-75	% yard (0.80m)	
(C) Tossed Flowers		White	4697-01	1% yards (1.49m)	
(D) Tossed Flowers		Blue	4697-75	¾ yard (0.34m)	
(E) Dots		White	4698-01	1½ yards (1.03m)	
(F) Dots		Red	4698-88*	% yard (0.57m)	
(G) Flowers		Blue	4699-75	% yard (0.80m)	
(H) Flowers		Red	4699-88	1⅓ yards (1.22m)	
(I) Geometric		White	4700-01	1⅓ yards (1.22m)	
* includes binding					
(A)	(B)	(C)	(D)	(E) (F)	(G)
(H)	(1)				
Backing (Purchased Separately)					
44" (1.12m					
) wide				
Flowers) wide		White	4699-01	3% yards (3.54m)
Flowers OR) wide		White	4699-01	3% yards (3.54m)
			White	4699-01	3% yards (3.54m) 1% yards (1.71m)
OR			White	4699-01	-
OR 108" (2.74r	n) wide	:	White	4699-01	-

All possible care has been taken to ensure the accuracy of this pattern. We are not responsible for printing errors or the manner in which individual work varies.

Please read the instructions carefully before starting this project. If kitting it is recommended a sample is made to confirm accuracy.



Cutting Instructions

Notes:

- Please make sure to check *blankquilting.net* for pattern updates prior to starting the project.
- All strips are cut across the width of fabric (WOF) from selvage to selvage edge unless otherwise noted.

Fabric A, cut:

(6) 3½" x WOF

- Set aside 3 strips for strip sets
- Subcut (60) 2" x 3½" rectangles

Fabrics B and **G**, from each cut: (12) 2" x WOF for strip sets

Fabrics C, cut: (2) 5" x WOF; subcut (15) 5" squares (18) 2" x WOF

- Set aside 12 strips for the strip sets
- Subcut 6 strips into (120) 2" squares

Fabric D, cut: (2) 5" x WOF; subcut (15) 5" squares

Fabric E, cut: (3) 6½" x WOF; subcut (60) 2" x 6½" rectangles (6) 2" x WOF; subcut (120) 2" squares

Fabric F, cut: (7) 2¹/₂" x WOF for binding

Fabrics H and **I**, from each cut: (5) 8" x WOF; subcut (15) 8" squares



SEWING

Note: All seam allowances are ¼" (0.64cm). Sew pieces with right sides together. Press seam allowances open unless otherwise indicated.

1. Sew a 2" **Fabric C** strip to a 2" **Fabric G** strip. Press the seam toward the darker fabric. Make 6 strip sets. Crosscut the strip sets into (120) 2" segments. Sew the segments in pairs and press the seams in one direction. Make (60) 3½" X units.

Repeat this step with (6) 2" **Fabric C** and (6) 2" **Fabric B** strips to make (60) 3½" Y units, and (3) 2" **Fabric B** and (3) 2" **Fabric G** strips to make (30) 3½" Z units (**Fig. 1**).



2. Draw two diagonal lines on the wrong side of the 5" Fabric C squares (a). Layer a marked Fabric C square atop a 5" Fabric D square.Stitch¼"fromeachsideofthediagonal lines (b), cut vertically and horizontally to make four equal squares (c), then cut each square on the drawn lines to make eight half-square triangles (d). Press open and trim dog ears. Repeat with the remaining Fabrics C and D squares to make (120) 2" half-square triangles (HST). Sew the HSTs in pairs as shown to make (60) 2" x 3½" units (Fig. 2).



 Sew a 2" Fabric E square to opposite ends of the step 2 units. Press the seams away from the center. Sew a 2" x 6½" Fabric E rectangle to the bottom. Press the seams toward the rectangle (Fig. 3).



 Gather the X and Y units. Sew an X unit to the left and a Y unit to the right of each step 4 unit. Press the seams toward the center. Make (60) 3½" x 12½" rows (Fig. 4).



All possible care has been taken to ensure the accuracy of this pattern. We are not responsible for printing errors or the manner in which individual work varies.

Please read the instructions carefully before starting this project. If kitting it is recommended a sample is made to confirm accuracy.

Fabrics H and I to make (120) 3¹/₂" HSTs. Draw a diagonal line on the wrong side of (120) 2" Fabric C squares. With right sides together, place a marked Fabric C square on the darker corner of an HST and stitch on the drawn line. Trim the seam allowance to ¼" and press open toward the corner. Repeat with the remaining HSTs. Sew the units together in pairs as shown. Make (60) 3½" x 6½" rectangles (**Fig. 5**).



5. Repeat step 2 with the 8" squares of 7. Sew a step 3 rectangle to either side of a block center, noting fabric orientation. Press the seams away from the center. Sew a step 5 row to the top and bottom as shown. Press the seams in one direction. Repeat to complete (30) 12½" blocks (Fig. 7).

babric of inspiration



Make 30 Fig. 7

6. Sew a 3¹/₂" **Fabric A** strip between a 2" strip each of **Fabrics B** and **G** to make a strip set as in step 1. Press the seams toward the center. Make 3. Crosscut into (60) 2" segments. Sew a 2" x 31/2" Fabric A rectangle to either side of a step 1 unit Z. Press seams away from center. Repeat with all units Z. Add a segment to the top and bottom of each unit to make (30) 61/2" block centers (Fig. 6).



OUILT TOP ASSEMBLY

Note: Follow the Quilt Layout Diagram (page 7) while assembling the quilt top.

8. Referring to the quilt image for block placement and orientation, lay out 6 rows of 5 blocks. Join the blocks together in each row. Press the seams in opposite directions from row to row. Nesting adjacent seams, sew the rows together in order. Press.

All possible care has been taken to ensure the accuracy of this pattern. We are not responsible for printing errors or the manner in which individual work varies. Please read the instructions carefully before starting this project. If kitting it is recommended a sample is made to confirm accuracy. All free projects are intended to remain free and are not for resale.



FINISHING

- Sew together the (7) 2½" Fabric F binding strips end to end using diagonal seams. Press the seams open. Press the binding strip in half with the wrong sides together.
 Layer the backing (wrong side up), batting, and quilt top (right side up). Baste the layers
- together and quilt as desired. Trim excess batting and backing even with the top of the quilt.
- 11. Leaving an 8" tail of binding and beginning along an edge of the quilt top, matching the raw edges of the binding to the raw edges of the quilt. Sew the binding to the outside edge around all four sides and miter corners. Stop sewing approximately 12" from where you started and backstitch.
- 12.Lay both loose ends of the binding flat along the quilt edge. Where these two loose ends meet, fold them back onto themselves and press to form a crease. Using this crease as your stitching line, sew the two open ends of the binding together, with the right sides matching. Trim the seam to ¹/₄" and press it open. Finish sewing the binding to the quilt.
- 13. Turn the binding over the raw edge to the back of the quilt and hand or machine stitch in place.



Quilt Layout



All possible care has been taken to ensure the accuracy of this pattern. We are not responsible for printing errors or the manner in which individual work varies. Please read the instructions carefully before starting this project. If kitting it is recommended a sample is made to confirm accuracy. All free projects are intended to remain free and are not for resule